

## VestaEco FLOOR / FLOOR R


Sound insulating base for floating floors:  
boards, panels and laminates.

Evens out surface imperfections up to 3 mm and insulates footstep sounds. The use of natural resources during the production process results in a 100% eco-friendly material that does not emit any harmful substances into the room. Available with aluminium foil layer which reflects the heat back towards inside (FLOOR R).



### Advantages of the product:

- Healthy, eco-friendly material based on natural resources
- Perfect impact sounds insulation
- Allows to even out imperfections of the surface
- High compressive strength
- Does not absorb water
- Eco-friendly production process, thanks to the use of innovative, patented DefibraTech 1.0 technology



## AVAILABLE DIMENSIONS

Product name	Dimensions (mm)	Thickness (mm)	Pieces / pallet	m <sup>2</sup> / pallet	kg/m <sup>2</sup>	kg/pallet
VestaEco FLOOR / R	600x800	5	960 (*)	460,8	1,3	599
VestaEco FLOOR / R	600x800	7	686 (**)	329,3	1,8	599

(\*) 20 pcs. in a package

(\*\*) 15 pcs. in a package

## TECHNICAL PARAMETERS

Parameter	Value
Density	Approx. 260 kg/m <sup>3</sup>
Thermal conductivity coefficient $\lambda$	0,050 W/(m <sup>2</sup> K)
Thermal capacity C	2100 J/(kg <sup>2</sup> K)
Diffusion resistance factor $\mu$	5
Short-term water absorption	<1 kg/m <sup>2</sup>
Compression strength	100 kPa
Fire classification	E
Components	lignocellulosic fibres, cellulose fibres, PMDI resin
Material manufactured in compliance with the norm	PN-EN 13171